

## ECO- Solvent Inks

**Eco Series Inks ensure:**

- Vibrant, brilliant colors and Excellent color gamut
- Completely free of Hazardous Air Pollutants (HAPs), as defined in the Federal 1990 Clean Air Act
- Color and density consistency between different batches
- Two-year outdoor weather resistance
- Minimum maintenance whether the printer is in use or idle
- No clogged nozzles thus ensuring excellent print quality on a wide range of vinyl and paper substrates
- More than 18 months shelf time and less wear on the print heads
- More Competively priced

**Eco Series Inks:**

Item	<b>Suitable for the followings Solvent-based printers (All models):</b>
<b>ECO-360</b>	<b>Mimaki</b> JV3160S/JV3 160SP /JV3 250SP  <b>Roland</b> SOLJET PRO II 540/740,SJ-1000 EX,SJ-Pro II EX,PRO II EX - SJ-640/740 EX,PRO II EX - SC-540 EX and Roland VersaCAMM SP-300  <b>Mutoh</b> RockHopper I/II, Falcon II and Falcon Plus
<b>ECO-512</b>	All wide format plotters with piezo <b>Konica printhead</b> , including <b>Seiko</b> Colorpainter 64S/100S,HP9000s/10000s,DGI ST-1806
ECO cleaning solution	All wide format printers

**Physical Parameters:**

<b>Color</b>	C M Y K LM LC	<b>Solvent</b>	Ester
<b>Smell</b>	Slightly	<b>pH</b>	6.5-7.5
<b>Viscosity</b>	3-10cp	<b>Flash Point</b>	65°C
<b>Surface Tension</b>	25-35 dynes/cm	<b>Particle Size</b>	<0.2 $\mu$

**ECO Series Inks Hue :**




Ningbo MEC Industry And Trade Co., Ltd.

Tel : 0086-574-87383760

Fax : 0086-574-87383750

Email : [sales@nbmec.com](mailto:sales@nbmec.com) , [sales@signmaker.cn](mailto:sales@signmaker.cn)

Website: : [www.nbmec.com](http://www.nbmec.com) , [www.signmaker.cn](http://www.signmaker.cn)

---

**Package:**

220ml / cartridge, 440ml / cartridge, 1000ml / cartridge(For Seiko 64S/100S)), 1000ml / bottle

**Operational Specifications:**

Temperature:18 to 30°C/64 to 86 °F

Relative Humidity:25 to 60% Non-condensing

**Storage Specifications:**

1. Eco Series ink should be stored indoors at a temperature between 5 and 30°C
2. Eco Series ink shelf-life is 12 months, when stored as above.
3. Care must be taken to avoid contamination of inks and substrates.
4. Check that the preheat settings are as recommended.

---

**Address** : 2/F,A29 Zone,Alley 166,Huancheng North Rd.(West Section),Jiangbei District,

Ningbo,Zhejiang, China      **Postal code:** 315020

**Tel:** (86) 574 87383760, 66831478    **Fax:** (86) 574 87383750